

a data line driving circuit capable of driving the data lines; and
an auxiliary data line driving circuit capable of driving the data lines
independently from the data line driving circuit.

2. (Amended) The electro-optical device according to Claim 1, all of the
data lines being connected to the data line driving circuit, and only a portion of the data
lines being selectively connected to the auxiliary data line driving circuit.

3. (Twice Amended) The electro-optical device according to Claim 1, at
least one of the data line driving circuit and the auxiliary data line driving circuit including
a decoder.

4. (Twice Amended) The electro-optical device according to Claim 1, at
least one of the data line driving circuit and the auxiliary data line driving circuit including
a shift register.

5. (Twice Amended) The electro-optical device according to Claim 1, at
least one of the data line driving circuit and the auxiliary data line driving circuit including
a latch circuit.

6. (Twice Amended) The electro-optical device according to Claim 1, at
least one of the data line driving circuit and the auxiliary data line driving circuit including
a D/A converter circuit.

8. (Twice Amended) The electro-optical device according to Claim 1, three
dots including an electro-optical element capable of emitting red, an electro-optical
element capable of emitting green, and an electro-optical element capable of emitting blue
comprise one pixel to enable a color display, and only a data line corresponding to a
particular color of the three colors is selectively connected to the auxiliary data line
driving circuit.

9. (Amended) The electro-optical device according to Claim 8, only a data line which corresponds to the particular color and which is located in a specific region of a screen being selectively connected to the auxiliary data line driving circuit.

10. (Twice Amended) The electro-optical device according to Claim 1, a full-dot display mode and a character display mode being switched so that the data line driving circuit is enabled when the full-dot display mode is selected and the auxiliary data line driving circuit is enabled when the character display mode is selected.

11. (Twice Amended) The electro-optical device according to Claim 1, further comprising a scan line driving circuit capable of driving the scan lines, and an auxiliary scan line driving circuit capable of driving the scan lines independently from the scan line driving circuit,

all of the scan lines being connected to the scan line driving circuit, and only a portion of the scan lines being selectively connected to the auxiliary scan line driving circuit.

12. (Amended) The electro-optical device according to Claim 11, at least one of the scan line driving circuit and the auxiliary scan line driving circuit including a decoder.

B2
cancel
13. (Twice Amended) The electro-optical device according to Claim 11, at least one of the scan line driving circuit and the auxiliary scan line driving circuit including a shift register.

16. (Twice Amended) The electro-optical device according to Claim 10, the number of grayscale levels being smaller when the character display mode is selected than when the full-dot display mode is selected.

B3
cancel

17. (Twice Amended) The electro-optical device according to Claim 10, a frame frequency being lower when the character display mode is selected than when the full-dot display mode is selected.

18. (Twice Amended) The electro-optical device according to Claim 10, all pixels being reset altogether when the full-dot display mode changes to the character display mode.

19. (Twice Amended) The electro-optical device according to Claim 1, the data lines being driven by switching between the data line driving circuit and the auxiliary data line driving circuit in a period during which scan lines of one screen are being driven.

20. (Amended) A method of driving an electro-optical device comprising a plurality of data lines and scan lines that are arranged in a matrix manner, and a plurality of electro-optical elements that are disposed correspondingly to intersections of the data lines and the scan lines, the method comprising:

switching between a data line driving circuit and an auxiliary data line driving circuit to drive the data lines, the data line driving circuit being capable of driving the data lines, the auxiliary data line driving circuit being capable of driving the data lines independently from the data line driving circuit.

21. (Amended) The method according to Claim 20, all of the data lines being connected to the data line driving circuit, and only a portion of the data lines being selectively connected to the auxiliary data line driving circuit.

22. (Twice Amended) The method according to Claim 20, at least one of the data line driving circuit and the auxiliary data line driving circuit including a decoder.

23. (Twice Amended) The method according to Claim 20, at least one of the data line driving circuit and the auxiliary data line driving circuit including a shift register.

24. (Twice Amended) The method according to Claim 20, at least one of the data line driving circuit and the auxiliary data line driving circuit including a latch circuit.

B3
cont

25. (Twice Amended) The method according to Claim 20, at least one of the data line driving circuit and the auxiliary data line driving circuit including a D/A converter circuit.

27. (Twice Amended) The method according to Claim 20, three dots including an electro-optical element capable of emitting red, an electro-optical element capable of emitting green, and an electro-optical element capable of emitting blue comprise one pixel to enable a color display, and only a data line corresponding to a particular color of the three colors is selectively connected to the auxiliary data line driving circuit.

28. (Amended) The method according to Claim 27, only a data line which corresponds to the particular color and which is located in a specific region of a screen being selectively connected to the auxiliary data line driving circuit.

B4
cont.

29. (Twice Amended) The method according to Claim 20, a full-dot display mode and a character display mode being switched so that the data line driving circuit is enabled when the full-dot display mode is selected and the auxiliary data line driving circuit is enabled when the character display mode is selected.

30. (Twice Amended) The method according to Claim 20, further comprising switching between a scan line driving circuit and an auxiliary scan line driving circuit to drive the scan lines, the scan line driving circuit to which all of the scan lines are connected being capable of driving the scan lines, the auxiliary scan line driving circuit to which only a portion of the scan lines is selectively connected being capable of driving the portion of the scan lines independently from the scan line driving circuit.

31. (Amended) The method according to Claim 30, wherein at least one of the scan line driving circuit and the auxiliary scan line driving circuit including a decoder.

32. (Twice Amended) The method according to Claim 30, at least one of the scan line driving circuit and the auxiliary scan line driving circuit including a shift register.

33. (Twice Amended) The method according to Claim 30, wherein, of the scan lines, only a scan line that is located in a specific region of a screen is selectively connected to the auxiliary scan line driving circuit.

34. (Twice Amended) The method according to Claim 30, a full-dot display mode and a character display mode being switched so that the data line driving circuit and the scan line driving circuit are enabled when the full-dot display mode is selected and the auxiliary data line driving circuit and the auxiliary scan line driving circuit are enabled when the character display mode is selected.

35. (Twice Amended) The method according to Claim 29, the number of grayscale levels being smaller when the character display mode is selected than when the full-dot display mode is selected.

36. (Twice Amended) The method according to Claim 29, a frame frequency being lower when the character display mode is selected than when the full-dot display mode is selected.

37. (Twice Amended) The method according to Claim 29, all pixels being reset altogether when the full-dot display mode changes to the character display mode.

38. (Twice Amended) The method according to Claim 20, the data lines being driven by switching between the data line driving circuit and the auxiliary data line driving circuit in a period during which scan lines of one screen are being driven.

39. (Amended) An organic electroluminescent display device, comprising:

a plurality of row lines and a plurality of data lines that are arranged in a matrix manner;

a plurality of organic electroluminescent elements that are disposed correspondingly to intersections of the row lines and the data lines;

a data line driving circuit capable of driving the data lines;

a row driving circuit capable of driving the row lines; and

an auxiliary data line driving circuit, independent from the data line driving circuit, that drives the data lines, the auxiliary data line driving circuit including a decoder, wherein all of the data lines are connected to the data line driving circuit and only a portion of the data lines is selectively connected to the auxiliary data line driving circuit.

40. (Amended) An organic electroluminescent display device, comprising:

a plurality of row lines and a plurality of data lines that are arranged in a matrix manner;

a plurality of organic electroluminescent elements that are disposed correspondingly to intersections of the row lines and the data lines;

a data line driving circuit capable of driving the data lines;

a row driving circuit capable of driving the row lines; and

an auxiliary data line driving circuit, independent from the data line driving circuit, that drives the data lines, the auxiliary data line driving circuit including a shift register, wherein all of the data lines are connected to the data line driving circuit and only a portion of the data lines is selectively connected to the auxiliary data line driving circuit.

41. (Twice Amended) The organic electroluminescent display device according to Claim 39, the data line driving circuit including a shift register.

42. (Twice Amended) The organic electroluminescent display device according to Claim 39, the row driving circuit including a decoder.

44. (Twice Amended) The organic electroluminescent display device according to Claim 39, three dots including an organic electroluminescent element capable of emitting red, an organic electroluminescent element capable of emitting green, and an organic electroluminescent element capable of emitting blue comprise one pixel to enable a color display, and only a data line corresponding to a particular color of the three colors is selectively connected to the auxiliary data line driving circuit.

45. (Amended) The organic electroluminescent display device according to Claim 44, the particular color being green.

46. (Twice Amended) The organic electroluminescent display device according to Claim 44, only a data line which corresponds to the particular color and which is located in a specific region of a screen being selectively connected to the auxiliary data line driving circuit.

47. (Twice Amended) The organic electroluminescent display device according to Claim 39, a full-dot display mode and a character display mode being switched so that the data line driving circuit is enabled when the full-dot display mode is selected and the auxiliary data line driving circuit is enabled when the character display mode is selected.

48. (Twice Amended) The organic electroluminescent display device according to Claim 39, further comprising an auxiliary row line driving circuit, independent from the row driving circuit, that drives the row lines, the auxiliary row driving circuit including a decoder, wherein all of the row lines are connected to the row driving circuit and only a portion of the row lines is selectively connected to the auxiliary row driving circuit.

49. (Twice Amended) The organic electroluminescent display device according to Claim 39, further comprising an auxiliary row driving circuit, independent

from the row driving circuit, that drives the row lines, the auxiliary row driving circuit including a shift register, wherein all of the row lines are connected to the row driving circuit and only a portion of the row lines is selectively connected to the auxiliary row driving circuit.

51. (Twice Amended) ~~The organic electroluminescent display device~~

according to Claim 49, a full-dot display mode and a character display mode being switched so that the data line driving circuit and the row driving circuit are enabled when the full-dot display mode is selected and the auxiliary data line driving circuit and the auxiliary row driving circuit are enabled when the character display mode is selected.

52. (Twice Amended) The organic electroluminescent display device

according to Claim 47, the number of grayscale levels being smaller when the character display mode is selected than when the full-dot display mode is selected.

53. (Twice Amended) The organic electroluminescent display device

according to Claim 47, a frame frequency being lower when the character display mode is selected than when the full-dot display mode is selected.

54. (Twice Amended) The organic electroluminescent display device

according to Claim 47, all pixels being reset altogether when the full-dot display mode changes to the character display mode.

55. (Twice Amended) The method according to Claim 20, the data lines

being driven by switching between the data line driving circuit and the auxiliary data line driving circuit in one horizontal scan period.

56. (Twice Amended) An electronic apparatus comprising a display device

for displaying data,

said display device comprising an electro-optical display device using the

electro-optical device according to Claim 1, or the organic electroluminescent display

device comprising: a plurality of row lines and a plurality of data lines which are arranged in a matrix manner; organic electroluminescent elements which are disposed correspondingly to intersections of the row lines and the data lines; a data line driving circuit capable of driving the data lines; a row driving circuit capable of driving the row lines; and

an auxiliary data line driving circuit, independent from the data line driving circuit, that drives the data lines, the auxiliary data line driving circuit including a decoder, all of the data lines being connected to the data line driving circuit and only a portion of the data lines being selectively connected to the auxiliary data line driving circuit.

all concl

Please add new claims 57-67 as follows:

--57. The electro-optical device according to Claim 15, the number of grayscale levels being smaller when the character display mode is selected than when the full-dot display mode is selected.--

--58. The electro-optical device according to Claim 15, a frame frequency being lower when the character display mode is selected than when the full-dot display mode is selected.--

all concl

--59. The electro-optical device according to Claim 15, all pixels being reset altogether when the full-dot display mode changes to the character display mode.--

--60. The method according to Claim 34, the number of grayscale levels being smaller when the character display mode is selected than when the full-dot display mode is selected.--

--61. The method according to Claim 34, a frame frequency being lower when the character display mode is selected than when the full-dot display mode is selected.--

--62. The method according to Claim 34, all pixels being reset altogether when the full-dot display mode changes to the character display mode.--

--63. The organic electroluminescent display device according to Claim 40, the data line driving circuit including a shift register.--

--64. The organic electroluminescent display device according to Claim 40, the row driving circuit including a decoder.--

--65. The organic electroluminescent display device according to Claim 40, wherein, of the data lines, only a data line that is located in a specific region of a screen is selectively connected to the auxiliary data line driving circuit.

--66. The organic electroluminescent display device according to Claim 40, three dots including an organic electroluminescent element capable of emitting red, an organic electroluminescent element capable of emitting green, and an organic electroluminescent element capable of emitting blue comprise one pixel to enable a color display, and only a data line corresponding to a particular color of the three colors is selectively connected to the auxiliary data line driving circuit.--

--67. The organic electroluminescent display device according to Claim 66, the particular color being green.--

REMARKS

Claims 1-67 are pending in this Application. By this Supplemental Preliminary Amendment, the Abstract, specification and claims 1-6, 8-13, 16-25, 27-42, 44-49 and 51-56 are amended. Additionally, new claims 57-67 are added. No new matter is added. Prompt and favorable consideration on the merits is respectfully requested.

The attached Appendix includes marked-up copies of the substitute specification (37 C.F.R. §1.125(b)(ii)) and claims (37 C.F.R. §1.121(c)(1)(ii)).